## Shanghai Leadgo-Tech Co.,Ltd.

地址: 上海浦东康桥东路1365弄18号 POST: 201319 ADD: 18#, NO.1365,East Kangqiao Road.Pudong Area.Shanghai 201319 China TEL:0086(0)21 68183116 68183117 68183118 Fax:0086(0)21 68183100

Document NO.: LG-YF-PT-01 Edition: A/2



# Flashtape 200S-1

### **◆** DESCRIPTION

Flashtape 200S-1 is made of polyester tape backed with a fully solidified pressure silicone adhesive. Flashtape 200S is commonly used to keep all bagging materials plies in place like peel ply, release film and breathers. Flashtape 200S is also used to protect tooling parts and some component areas from flush of resin. Flashtape 200S thicknesses are below.

### **♦ PROPERTIES**

Reference	Flashtape 200S-1
Maximum Cure Temperature	200°C with Silicone adhesive
Basic	Polyester
Colour	Blue
Adhesive	Silicone
Tape Thickness	$0.068$ mm $\pm 0.01$
Adhesive Thickness	$0.043 \text{mm} \pm 0{,}005$
Support Thickness	$0.025$ mm $\pm 0,005$
Widths / Length	25mm-50mm / 66m
Adhesion (N/25mm)	8 ± 3,5

#### **◆** AVAILABILITY&PACKAGING

Roll sizes:	25mm*66m
	50mm*66m

Other size on request.

### **♦** Notes

Shelf life: 12 months

Storage: In dry area at room temperature.