Shanghai Leadgo-Tech Co.,Ltd.

地址: 上海浦东康桥东路1365弄18号 POST: 201319 ADD: 18#, NO.1365,East Kangqiao Road.Pudong Area.Shanghai 201319 China TEL:0086(0)21 68183116 68183117 68183118 Fax:0086(0)21 68183100

Document NO.: LG-YF-VI-05 $\,$ Edition: A/O $\,$

♦ **DESCRIPTION**

VI250E is a high economical extruded infusion mesh, is compatible with most substrate including composite moulds and films, applies to vacuum infusion operation at room temperature.

♦ CHARACTERISTIC

- Excellent operability, good flatness
- Well uniformity, long time resistance

PROPERTIES

Specifications	
Colour	Green
Thickness/in	0.055(1.4mm)
Width/in	79(2m)
Maximum Use Temperature/°F	250(120°C)

RECOMMENDED PROCESS

VI250E has good flatness and excellent operability, recommend being used below 250°F.

♦ STORAGE

VI250E is packed in roll. Recommend being packed in polyethylene bag or any other materials which have the same function, used and stored in a clean and relative humidity environment about 30%-70%RH and 41%-77%F.

Characteristics given in this TDS are for information only and help to make a choice. End users should validate the use of products according their own tests and findings. In any case these values or information shall be taken to engage responsibility of LEADGO companies. Model specifications, product information is subject to change without any further notice.

