Shanghai Leadgo-Tech Co.,Ltd.

地址: 上海浦东康桥东路1365弄18号 POST: 201319 ADD: 18#, NO.1365,East Kangqiao Road.Pudong Area.Shanghai 201319 China TEL:0086(0)21 68183116 68183117 68183118 Fax:0086(0)21 68183100



LEADPLEX-1

DESCRIPTION

The LEADPLEX-1 kit is made up of flow mesh and release film, which is particularly suitable for using in fan blades and hull large molds, it can save time, and it is also used in other hand lay-up and resin diversion processes.

◆ CHARACTERISTIC

- · Surface smooth, no impurities, easy to shop paste
- · Easy to peel
- Save time

♦ PROPERTIES

| Specifications | |
|-------------------------|---------------------|
| Colour | White and blue |
| Material | VI160W+LRF150B(P16) |
| Adhesion agent | PU |
| Width | 1500mm(4.9') |
| Planar density | 195g/m2 |
| Maximum Use Temperature | 248°F(120°C) |

► RECOMMENDED PROCESS

LEADPLEX-1 stripping performance is good. It is recommend to be used in cure process below 120°C.

► STORAGE

LEADPLEX-1 Kit is packed in roll and in polyethylene bag, or other materials that have same performances, stored in a clean and humid environment with 30%-70% RH and 5°C-25°C temperature.

Characteristics given in this TDS are for information only and help to make a choice. End users should validate the use of products according their own tests and findings. In any case these values or information shall be taken to engage responsibility of LEADGO companies. Model specifications, product information is subject to change without any further notice.