Shanghai Leadgo-Tech Co.,Ltd.

地址: 上海浦东康桥东路1365弄18号 POST: 201319 ADD: 18#, NO.1365, East Kangqiao Road. Pudong Area. Shanghai 201319 China TEL:0086(0)21 68183116 68183117 68183118 Fax:0086(0)21 68183100

Document NO.: LG-YF-KT-37 Edition: A/O



LEADPLEX4

DESCRIPTION

LEADPLEX4 is an assembled structure of breather, perforated release film and peel ply. It absorbs excess resin and volatiles from vacuum bagging equipment and has excellent release properties.

CHARACTERISTIC

- Excellent operability, good flatness
- Good air permeability
- Well uniformity, long time resistance
- Excellent release characteristics

PROPERTIES

Specifications	
Colour	Blue+White with red tracer yarn
Thickness/in	0.04(1mm)
Width/in	59(1.5m)
Maximum Use Temperature/°F	300(150°C)
Weight/[g/m ²]	$260~\mathrm{g/m^2}$

◆ RECOMMENDED PROCESS

LEADPLEX4 has good flatness and excellent operability, recommend being used below 300°F.

STORAGE

LEADPLEX4 is packed in roll. Recommend being packed in polyethylene bag or any other materials which have the same function, used and stored in a clean and relative humidity environment about 30%-70%RH and 41°F-77°F.